



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/775,913	02/10/2004	Joseph J. Bergmeister	210421US01 (4081-08200)	1222
37814 7590 09/10/2007 CHEVRON PHILLIPS CHEMICAL COMPANY 5601 Granite Parkway, Suite 750 PLANO, TX 75024			EXAMINER BOYER, RANDY	
			ART UNIT 1764	PAPER NUMBER
			MAIL DATE 09/10/2007	DELIVERY MODE PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary

Application No.

10/775,913

Applicant(s)

BERGMEISTER ET AL.

Examiner

Randy Boyer

Art Unit

1764

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 15 August 2007.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-4,6-22 and 24-49 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-4,6-22 and 24-49 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
- ☐ Certified copies of the priority documents have been received.
 - ☐ Certified copies of the priority documents have been received in Application No. _____.
 - ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|---|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| 3) <input checked="" type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)
Paper No(s)/Mail Date <u>15 August 2007</u> . | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Response to Amendment

1. Examiner acknowledges response filed 15 August 2007 containing amendments to the claims, remarks, and Information Disclosure Statement.
2. All previous rejections are withdrawn in view of Applicant's arguments and amendment to the claims.
3. New grounds for rejection of claims 1-4, 6-22, and 24-49 are entered. The rejections follow.

Claim Rejections - 35 USC § 102

4. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office Action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

5. Claims 1-4, 9-16, 19-22, 27-34, 37, 38, and 44-48 are rejected under 35 U.S.C. 102(b) as being anticipated by Johnson (US 4404124).
6. With respect to claim 1, Johnson discloses a catalyst for the selective hydrogenation of acetylene (see Johnson, Abstract), comprising: (a) an alumina support (see Johnson, column 2, lines 35-37) having a uniformly round external surface (e.g. in the shape of "pills" (see Johnson, column 3, lines 14-15; and Example I)), a surface

Art Unit: 1764

area in the range of about 3 to about 10 square meters per gram, a pore volume of about 0.24 to about 0.64 cubic centimeters per gram, and an average pore diameter from about 600 Angstroms to about 5000 Angstroms (see Johnson, column 2, lines 35-42); (b) palladium in the range of about 0.01 to 1.0 weight percent of the catalyst, wherein substantially all of the palladium is concentrated in a skin periphery of the catalyst, and wherein the skin has a thickness less than about 400 microns (see Johnson, column 2, lines 21-31); and (c) silver in the range of about 0.5 to 10.0 times the weight of the palladium (see Johnson, column 2, lines 21-31).

Examiner notes that Johnson does not explicitly disclose wherein less than 80 weight percent of the silver is present in the skin periphery. However, Johnson discloses wherein the silver is distributed throughout the catalyst (see Johnson, column 3, lines 31-32), while only the palladium is concentrated in the skin periphery of the catalyst (see Johnson, column 2, lines 21-31).

Therefore, Examiner finds Applicant's limitation "wherein less than 80 weight percent of the silver is present in the skin periphery" to be inherent within the disclosure of Johnson.

When an examiner has reason to believe that the functional language asserted to be critical for establishing novelty in claimed subject matter may in fact be an inherent characteristic of the prior art, the burden of proof is shifted to Applicant to prove that the subject matter not shown in the prior art does not possess the characteristics relied upon. See MPEP § 2112(V) (citing In re Fitzgerald, 619 F.2d 67, 70 (CCPA 1980)).

Art Unit: 1764

7. With respect to claims 2-4, Johnson discloses wherein the catalyst can be of *any* suitable shape and dimensions (see Johnson, column 3, lines 14-15), e.g. "pills" (see Johnson, Example I).

8. With respect to claim 9, Johnson discloses wherein the dimensions of the catalyst particles are in the range of about 2 to about 8 millimeters (see Johnson, column 3, lines 14-20).

9. With respect to claims 10 and 11, Johnson discloses wherein the weight ratio of silver to palladium is in the range of about 0.5 to about 8 (see Johnson, column 2, lines 21-31).

10. With respect to claim 12, Johnson discloses wherein the catalyst contains about 0.01 to 0.5 weight percent palladium (see Johnson, column 2, lines 21-25).

11. With respect to claim 13, Johnson discloses wherein the catalyst is prepared by impregnating alumina particles with a solution of palladium chloride (see Johnson, Example I).

12. With respect to claim 14, Johnson discloses wherein the catalyst is prepared by mixing the catalyst particles with an aqueous solution of silver nitrate (see Johnson, Example I).

13. With respect to claim 15, Johnson discloses wherein a selectivity of the catalyst for the conversion of acetylene to ethylene is greater than 40% (see Johnson, Fig. 1 and accompanying text).

14. With respect to claim 16, Johnson discloses wherein the palladium is less than 0.05 weight % of the catalyst (see Johnson, column 2, lines 21-31).

Art Unit: 1764

15. With respect to claim 19, Johnson discloses a method for the treatment of a gaseous mixture comprising acetylene (see Johnson, column 2, lines 1-9), which method comprises selectively hydrogenating the acetylene therein by contacting the mixture together with hydrogen with a catalyst (see Johnson, Example II); wherein the catalyst comprises an alumina support (see Johnson, column 2, lines 35-37) having a uniformly round external surface (e.g. in the shape of "pills" (see Johnson, column 3, lines 14-15; and Example I)), a surface area in the range of about 3 to about 10 square meters per gram, a pore volume of about 0.24 to about 0.64 cubic centimeters per gram and has an average pore diameter from about 600 Angstroms to about 5000 Angstroms (see Johnson, column 2, lines 35-42); wherein the catalyst comprises palladium in the range of about 0.01 to 1.0 weight percent of the catalyst, wherein substantially all of the palladium is concentrated in a skin periphery of the catalyst, wherein the skin has a thickness less than about 400 microns (see Johnson, column 2, lines 21-31); and wherein the catalyst comprises silver in the range of about 0.5 to 10.0 times the weight of the palladium (see Johnson, column 2, lines 21-31).

Examiner notes that Johnson does not explicitly disclose wherein less than 80 weight percent of the silver is present in the skin periphery. However, Johnson discloses wherein the silver is distributed throughout the catalyst (see Johnson, column 3, lines 31-32), while only the palladium is concentrated in the skin periphery of the catalyst (see Johnson, column 2, lines 21-31).

Art Unit: 1764

Therefore, Examiner finds Applicant's limitation "wherein less than 80 weight percent of the silver is present in the skin periphery" to be inherent within the disclosure of Johnson.

When an examiner has reason to believe that the functional language asserted to be critical for establishing novelty in claimed subject matter may in fact be an inherent characteristic of the prior art, the burden of proof is shifted to Applicant to prove that the subject matter not shown in the prior art does not possess the characteristics relied upon. See MPEP § 2112(V) (citing *In re Fitzgerald*, 619 F.2d 67, 70 (CCPA 1980)).

16. With respect to claims 20-22, Johnson discloses wherein the catalyst can be of any suitable shape and dimensions (see Johnson, column 3, lines 14-15), e.g. "pills" (see Johnson, Example I).

17. With respect to claim 27, Johnson discloses wherein the gaseous mixture contains less than about 1000 ppm of carbon monoxide (see Johnson, Table I).

18. With respect to claims 28 and 30, Johnson discloses wherein the weight ratio of silver to palladium is in the range of about 0.5 to about 8 (see Johnson, column 2, lines 21-31).

19. With respect to claim 29, Johnson discloses wherein the dimensions of the catalyst particles are in the range of about 2 to about 8 millimeters (see Johnson, column 3, lines 14-20).

20. With respect to claim 31, Johnson discloses wherein the hydrogenation temperature is in the range of about 35°C to about 150°C (see Johnson, column 3, lines

Art Unit: 1764

67-68; and column 4, line 1) and the space velocity is in the range of about 1,000 hr⁻¹ to about 20,000 hr⁻¹ (see Johnson, column 4, lines 5-8).

21. With respect to claim 32, Johnson discloses wherein the gaseous mixture contains no more than about 800 ppm of carbon monoxide (see Johnson, Table I).

22. With respect to claim 33, Johnson discloses wherein the catalyst is prepared by (a) impregnating alumina particles with a solution of palladium chloride (see Johnson, Example I), (b) calcining the impregnated alumina particles (see Johnson, Example I); and (c) mixing the particles with an amount of an aqueous solution of silver nitrate in excess of the pore volume of the alumina (see Johnson, Example I).

23. With respect to claim 34, Johnson discloses wherein the catalyst contains about 0.01 to 10 weight % palladium (see Johnson, column 2, lines 21-31).

24. With respect to claim 37, Johnson discloses wherein a selectivity of the catalyst for the conversion of acetylene to ethylene is greater than 40% (see Johnson, Fig. 1 and accompanying text).

25. With respect to claim 38, Johnson discloses wherein the palladium is less than 0.05 weight % of the catalyst (see Johnson, column 2, lines 21-31).

26. With respect to claims 44 and 45, Johnson discloses wherein less than about 70 weight percent of the silver is present in the skin periphery (see Johnson, column 2, lines 21-31; and column 3, lines 31-32).

27. With respect to claim 46, Johnson discloses wherein the gas hourly space velocity of the gaseous mixture is 10,000 liters of feed per liter of catalyst per hour (see Johnson, column 4, lines 4-8).

Art Unit: 1764

28. With respect to claims 47 and 48, Johnson discloses wherein the pore volume is in a range of from about 0.24 to about 0.29 cubic centimeters per gram (see Johnson, column 2, lines 35-42).

Claim Rejections - 35 USC § 103

29. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office Action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

30. The factual inquiries set forth in *Graham v. John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:

1. Determining the scope and contents of the prior art.
2. Ascertaining the differences between the prior art and the claims at issue.
3. Resolving the level of ordinary skill in the pertinent art.
4. Considering objective evidence present in the application indicating obviousness or nonobviousness.

31. This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to

Art Unit: 1764

consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior art under 35 U.S.C. 103(a).

32. Claims 1-4, 9-16, 19-22, 27-38, and 44-48 are rejected under 35 U.S.C. 103(a) as being unpatentable over Johnson (US 4404124).

33. With respect to claim 1, Johnson discloses a catalyst for the selective hydrogenation of acetylene (see Johnson, Abstract), comprising: (a) an alumina support (see Johnson, column 2, lines 35-37) having a uniformly round external surface (e.g. in the shape of "pills" (see Johnson, column 3, lines 14-15; and Example I)), a surface area in the range of about 3 to about 10 square meters per gram, a pore volume of about 0.24 to about 0.64 cubic centimeters per gram, and an average pore diameter from about 600 Angstroms to about 5000 Angstroms (see Johnson, column 2, lines 35-42); (b) palladium in the range of about 0.01 to 1.0 weight percent of the catalyst, wherein substantially all of the palladium is concentrated in a skin periphery of the catalyst, and wherein the skin has a thickness less than about 400 microns (see Johnson, column 2, lines 21-31); and (c) silver in the range of about 0.5 to 10.0 times the weight of the palladium (see Johnson, column 2, lines 21-31).

Johnson does not explicitly disclose wherein less than 80 weight percent of the silver is present in the skin periphery.

However, Johnson discloses wherein the silver is "distributed throughout the catalyst in any suitable manner" (see Johnson, column 3, lines 31-32), while only the palladium is concentrated in the skin periphery of the catalyst (see Johnson, column 2, lines 21-31).

Art Unit: 1764

Therefore, Examiner finds Applicant's limitation "wherein less than 80 weight percent of the silver is present in the skin periphery" to be of no patentable consequence in view of the teachings of Johnson.

34. With respect to claims 2-4, Johnson discloses wherein the catalyst can be of *any* suitable shape and dimensions (see Johnson, column 3, lines 14-15), e.g. "pills" (see Johnson, Example I).

35. With respect to claim 9, Johnson discloses wherein the dimensions of the catalyst particles are in the range of about 2 to about 8 millimeters (see Johnson, column 3, lines 14-20).

36. With respect to claims 10 and 11, Johnson discloses wherein the weight ratio of silver to palladium is in the range of about 0.5 to about 8 (see Johnson, column 2, lines 21-31).

37. With respect to claim 12, Johnson discloses wherein the catalyst contains about 0.01 to 0.5 weight percent palladium (see Johnson, column 2, lines 21-25).

38. With respect to claim 13, Johnson discloses wherein the catalyst is prepared by impregnating alumina particles with a solution of palladium chloride (see Johnson, Example I).

39. With respect to claim 14, Johnson discloses wherein the catalyst is prepared by mixing the catalyst particles with an aqueous solution of silver nitrate (see Johnson, Example I).

Art Unit: 1764

40. With respect to claim 15, Johnson discloses wherein a selectivity of the catalyst for the conversion of acetylene to ethylene is greater than 40% (see Johnson, Fig. 1 and accompanying text).

41. With respect to claim 16, Johnson discloses wherein the palladium is less than 0.05 weight % of the catalyst (see Johnson, column 2, lines 21-31).

42. With respect to claim 19, Johnson discloses a method for the treatment of a gaseous mixture comprising acetylene (see Johnson, column 2, lines 1-9), which method comprises selectively hydrogenating the acetylene therein by contacting the mixture together with hydrogen with a catalyst (see Johnson, Example II); wherein the catalyst comprises an alumina support (see Johnson, column 2, lines 35-37) having a uniformly round external surface (e.g. in the shape of "pills" (see Johnson, column 3, lines 14-15; and Example I)), a surface area in the range of about 3 to about 10 square meters per gram, a pore volume of about 0.24 to about 0.64 cubic centimeters per gram and has an average pore diameter from about 600 Angstroms to about 5000 Angstroms, (see Johnson, column 2, lines 35-42); wherein the catalyst comprises palladium in the range of about 0.01 to 1.0 weight percent of the catalyst, wherein substantially all of the palladium is concentrated in a skin periphery of the catalyst, wherein the skin has a thickness less than about 400 microns (see Johnson, column 2, lines 21-31); and wherein the catalyst comprises silver in the range of about 0.5 to 10.0 times the weight of the palladium (see Johnson, column 2, lines 21-31).

Johnson does not explicitly disclose wherein less than 80 weight percent of the silver is present in the skin periphery.

However, Johnson discloses wherein the silver is "distributed throughout the catalyst in any suitable manner" (see Johnson, column 3, lines 31-32), while only the palladium is concentrated in the skin periphery of the catalyst (see Johnson, column 2, lines 21-31).

Therefore, Examiner finds Applicant's limitation "wherein less than 80 weight percent of the silver is present in the skin periphery" to be of no patentable consequence in view of the teachings of Johnson.

43. With respect to claims 20-22, Johnson discloses wherein the catalyst can be of any suitable shape and dimensions (see Johnson, column 3, lines 14-15), e.g. "pills" (see Johnson, Example I).

44. With respect to claim 27, Johnson discloses wherein the gaseous mixture contains less than about 1000 ppm of carbon monoxide (see Johnson, Table I).

45. With respect to claims 28 and 30, Johnson discloses wherein the weight ratio of silver to palladium is in the range of about 0.5 to about 8 (see Johnson, column 2, lines 21-31).

46. With respect to claim 29, Johnson discloses wherein the dimensions of the catalyst particles are in the range of about 2 to about 8 millimeters (see Johnson, column 3, lines 14-20).

47. With respect to claim 31, Johnson discloses wherein the hydrogenation temperature is in the range of about 35°C to about 150°C (see Johnson, column 3, lines 67-68; and column 4, line 1) and the space velocity is in the range of about 1,000 hr⁻¹ to about 20,000 hr⁻¹ (see Johnson, column 4, lines 5-8).

Art Unit: 1764

48. With respect to claim 32, Johnson discloses wherein the gaseous mixture contains no more than about 800 ppm of carbon monoxide (see Johnson, Table I).

49. With respect to claim 33, Johnson discloses wherein the catalyst is prepared by (a) impregnating alumina particles with a solution of palladium chloride (see Johnson, Example I), (b) calcining the impregnated alumina particles (see Johnson, Example I); and (c) mixing the particles with an amount of an aqueous solution of silver nitrate in excess of the pore volume of the alumina (see Johnson, Example I).

50. With respect to claim 34, Johnson discloses wherein the catalyst contains about 0.01 to 10 weight % palladium (see Johnson, column 2, lines 21-31).

51. With respect to claim 35, Johnson discloses wherein the catalyst is housed in a vessel; flowing acetylene through the vessel to contact the catalyst; and wherein the vessel comprises a means by which to maintain a vessel temperature within a predetermined range (see Johnson, Example II).

52. With respect to claim 36, Johnson discloses wherein the predetermined range is about 30°C to about 150°C (see Johnson, column 3, lines 67-68; and column 4, line 1).

53. With respect to claim 37, Johnson discloses wherein a selectivity of the catalyst for the conversion of acetylene to ethylene is greater than 40% (see Johnson, Fig. 1 and accompanying text).

54. With respect to claim 38, Johnson discloses wherein the palladium is less than 0.05 weight % of the catalyst (see Johnson, column 2, lines 21-31).

Art Unit: 1764

55. With respect to claims 44 and 45, Johnson discloses wherein less than about 70 weight percent of the silver is present in the skin periphery (see Johnson, column 2, lines 21-31; and column 3, lines 31-32).

56. With respect to claim 46, Johnson discloses wherein the gas hourly space velocity of the gaseous mixture is 10,000 liters of feed per liter of catalyst per hour (see Johnson, column 4, lines 4-8).

57. With respect to claims 47 and 48, Johnson discloses wherein the pore volume is in a range of from about 0.24 to about 0.29 cubic centimeters per gram (see Johnson, column 2, lines 35-42).

58. Claims 6-8, 17, 18, 24-26, 39-43, and 49 are rejected under 35 U.S.C. 103(a) as being unpatentable over Johnson (US 4404124) in view of Cheung (US 5489565). Alternatively, claims 6-8, 17, 18, 24-26, 39-43, and 49 are rejected under 35 U.S.C. 103(a) as being unpatentable over Johnson (US 4404124) in view of Cheung (US 5489565) as evidenced by Frenzel (WO 01/41922 A1).

59. With respect to claim 6, Johnson discloses a catalyst for the selective hydrogenation of acetylene (see Johnson, Abstract), comprising: (a) an alumina support (see Johnson, column 2, lines 35-37) having a uniformly round external surface (e.g. in the shape of "pills" (see Johnson, column 3, lines 14-15; and Example I)), a surface area in the range of about 3 to about 10 square meters per gram, a pore volume of about 0.24 to about 0.64 cubic centimeters per gram, and an average pore diameter from about 600 Angstroms to about 5000 Angstroms (see Johnson, column 2, lines 35-42); (b) palladium in the range of about 0.01 to 1.0 weight percent of the catalyst,

Art Unit: 1764

wherein substantially all of the palladium is concentrated in a skin periphery of the catalyst, and wherein the skin has a thickness less than about 400 microns (see Johnson, column 2, lines 21-31); and (c) silver in the range of about 0.5 to 10.0 times the weight of the palladium (see Johnson, column 2, lines 21-31).

Johnson does not explicitly disclose wherein less than 80 weight percent of the silver is present in the skin periphery; or wherein the catalyst further comprises an alkali metal present in the range of about 0.01 to 10 weight % of the catalyst.

However, Johnson discloses wherein the silver is "distributed throughout the catalyst in any suitable manner" (see Johnson, column 3, lines 31-32), while only the palladium is concentrated in the skin periphery of the catalyst (see Johnson, column 2, lines 21-31). In addition, Cheung discloses a selective hydrogenation catalyst comprises of palladium, silver, and an alkali metal fluoride in the range of 0.01 to 10 weight percent of the catalyst (see Cheung, Abstract; and column 3, lines 1-7). Cheung explains that such a catalyst is preferred over a hydrogenation catalyst comprised of only palladium and silver, e.g. to achieve improvements in selectivity and increase in catalyst life (see Cheung, column 1, lines 16-27; and entire disclosure). Moreover, catalysts of the type disclosed by Cheung (i.e. silver/palladium/alkali catalysts) are known in the art to be highly effective for the hydrogenation of highly unsaturated hydrocarbons such as acetylenes (see e.g. Frenzel, Abstract; and entire disclosure).

Therefore, the person having ordinary skill in the art of catalysts for the selective hydrogenation of acetylenes would have been motivated to modify the catalyst of Johnson by: (1) providing a catalyst wherein less than 80 weight percent of the silver is

present in the skin periphery, and (2) incorporating the use of an alkali metal component in the range of about 0.01 to 10 weight % of the catalyst (as taught by Cheung) in order to achieve improvements in catalyst selectivity and increase in catalyst life.

Finally, the person having ordinary skill in the art of catalysts for the selective hydrogenation of acetylene would have had a reasonable expectation of success in modifying the catalyst of Johnson to provide for a silver content in the skin periphery of less than 80 weight percent and use of an alkali metal component in the range of 0.01 to 10 weight % of the catalyst (as taught by Cheung) because (1) Johnson discloses wherein the silver may be "distributed *throughout* the catalyst in any suitable manner," (2) both Johnson and Cheung are concerned with catalysts for the selective hydrogenation of unsaturated hydrocarbons, (3) both Johnson and Cheung propose use of a silver/palladium hydrogenation catalyst, and (4) it is known in the art that silver/palladium/alkali metal catalysts are highly effective for the hydrogenation of highly unsaturated hydrocarbons such as acetylene (e.g. as evidenced by Frenzel).

60. With respect to claim 7, Cheung discloses a halide in the range of about 0.1 to 10 times the molar concentration of alkali metal present in the catalyst (see Cheung, column 3, lines 1-7).

61. With respect to claim 8, Cheung discloses wherein the alkali metal comprises potassium (see Cheung, column 3, lines 1-7).

62. With respect to claim 17, Johnson discloses wherein the selectivity of the catalyst for the conversion of acetylene to ethylene is greater than 50 % (see Johnson, Fig. 1 and accompanying text) (see also Frenzel, Table 2 (catalyst E)).

Art Unit: 1764

63. With respect to claim 18, Johnson discloses wherein the palladium is less than 0.03 weight % of the catalyst (see Johnson, column 2, lines 21-31).

64. With respect to claim 24, Johnson discloses a method for the treatment of a gaseous mixture comprising acetylene (see Johnson, column 2, lines 1-9), which method comprises selectively hydrogenating the acetylene therein by contacting the mixture together with hydrogen with a catalyst (see Johnson, Example II); wherein the catalyst comprises an alumina support (see Johnson, column 2, lines 35-37) having a uniformly round external surface (e.g. in the shape of "pills" (see Johnson, column 3, lines 14-15; and Example I)), a surface area in the range of about 3 to about 10 square meters per gram, a pore volume of about 0.24 to about 0.64 cubic centimeters per gram and has an average pore diameter from about 600 Angstroms to about 5000 Angstroms (see Johnson, column 2, lines 35-42); wherein the catalyst comprises palladium in the range of about 0.01 to 1.0 weight percent of the catalyst, wherein substantially all of the palladium is concentrated in a skin periphery of the catalyst, wherein the skin has a thickness less than about 400 microns (see Johnson, column 2, lines 21-31); and wherein the catalyst comprises silver in the range of about 0.5 to 10.0 times the weight of the palladium (see Johnson, column 2, lines 21-31).

Johnson does not explicitly disclose wherein less than 80 weight percent of the silver is present in the skin periphery; or wherein the catalyst further comprises an alkali metal present in the range of about 0.01 to 10 weight % of the catalyst.

However, Johnson discloses wherein the silver is "distributed throughout the catalyst in any suitable manner" (see Johnson, column 3, lines 31-32), while only the

Art Unit: 1764

palladium is concentrated in the skin periphery of the catalyst (see Johnson, column 2, lines 21-31). In addition, Cheung discloses a method for selective hydrogenation using a catalyst comprising palladium, silver, and an alkali metal fluoride in the range of 0.01 to 10 weight percent of the catalyst (see Cheung, Abstract; column 3, lines 1-7; and column 4, lines 22-65). Cheung explains that such a catalyst is preferred over a hydrogenation catalyst comprised of only palladium and silver, e.g. to achieve improvements in selectivity and increase in catalyst life (see Cheung, column 1, lines 16-27; and entire disclosure). Moreover, catalysts of the type disclosed by Cheung (i.e. silver/palladium/alkali catalysts) are known in the art to be highly effective for the hydrogenation of highly unsaturated hydrocarbons such as acetylenes (see e.g. Frenzel, Abstract; and entire disclosure).

Therefore, the person having ordinary skill in the art of methods for the treatment of gaseous mixtures comprising acetylene would have been motivated to modify the catalyst of Johnson by: (1) providing a catalyst wherein less than 80 weight percent of the silver is present in the skin periphery, and (2) incorporating the use of an alkali metal component in the range of about 0.01 to 10 weight % of the catalyst (as taught by Cheung) in order to achieve improvements in catalyst selectivity and increase in catalyst life.

Finally, the person having ordinary skill in the art of methods for the treatment of gaseous mixtures comprising acetylene would have had a reasonable expectation of success in modifying the catalyst of Johnson to provide for a silver content in the skin periphery of less than 80 weight percent and use of an alkali metal component in the

Art Unit: 1764

range of 0.01 to 10 weight % of the catalyst (as taught by Cheung) because (1) Johnson discloses wherein the silver may be "distributed *throughout* the catalyst in any suitable manner," (2) both Johnson and Cheung are concerned with methods for the selective hydrogenation of unsaturated hydrocarbons, (3) both Johnson and Cheung propose use of a silver/palladium hydrogenation catalyst, and (4) it is known in the art that silver/palladium/alkali metal catalysts are highly effective for the hydrogenation of highly unsaturated hydrocarbons such as acetylene (e.g. as evidenced by Frenzel).

65. With respect to claim 25, Cheung discloses a halide in the range of about 0.1 to 10 times the molar concentration of alkali metal present in the catalyst (see Cheung, column 3, lines 1-7).

66. With respect to claim 26, Cheung discloses wherein the alkali metal comprises potassium (see Cheung, column 3, lines 1-7).

67. With respect to claim 39, Johnson discloses wherein the selectivity of the catalyst for the conversion of acetylene to ethylene is greater than 50 % (see Johnson, Fig. 1 and accompanying text) (see also Frenzel, Table 2 (catalyst E)).

68. With respect to claim 40, Johnson discloses wherein the palladium is less than 0.03 weight % of the catalyst (see Johnson, column 2, lines 21-31).

69. With respect to claim 41, Johnson discloses a catalyst for the selective hydrogenation of acetylene, comprising: (a) an alpha alumina support (see Johnson, column 2, lines 35-37) having a uniformly round external surface (e.g. in the shape of "pills" (see Johnson, column 3, lines 14-15; and Example I)), a surface area in the range of about 3 to about 10 square meters per gram, a pore volume of about 0.24 to about

Art Unit: 1764

0.64 cubic centimeters per gram, and an average pore diameter from about 600 Angstroms to about 5000 Angstroms (see Johnson, column 2, lines 35-42); (b) palladium in the range of about 0.01 to 1.0 weight percent of the catalyst, wherein substantially all of the palladium is concentrated in a skin periphery of the catalyst, and wherein the skin has a thickness less than about 400 microns (see Johnson, column 2, lines 21-31); and (c) silver in the range of about 0.5 to 10.0 times the weight of the palladium (see Johnson, column 2, lines 21-31).

Johnson does not disclose wherein less than 80 weight percent of the silver is present in the skin periphery; or wherein the catalyst contains potassium in the range of about 0.01 to 10 weight % of the catalyst and fluoride in the range of about 0.1 to 10 times the molar concentration of potassium present in the catalyst.

However, Johnson discloses wherein the silver is "distributed throughout the catalyst in any suitable manner" (see Johnson, column 3, lines 31-32), while only the palladium is concentrated in the skin periphery of the catalyst (see Johnson, column 2, lines 21-31). In addition, Cheung discloses a selective hydrogenation catalyst comprises of palladium, silver, potassium in the range of 0.01 to 10 weight percent of the catalyst, and fluoride in an equimolar concentration with that of potassium present in the catalyst (see Cheung, Abstract; and column 3, lines 1-7). Cheung explains that such a catalyst is preferred over a hydrogenation catalyst comprised of only palladium and silver, e.g. to achieve improvements in selectivity and increase in catalyst life (see Cheung, column 1, lines 16-27; and entire disclosure). Moreover, catalysts of the type disclosed by Cheung (i.e. silver/palladium/alkali catalysts) are known in the art to be

Art Unit: 1764

highly effective for the hydrogenation of highly unsaturated hydrocarbons such as acetylenes (see e.g. Frenzel, Abstract; and entire disclosure).

Therefore, the person having ordinary skill in the art of catalysts for the selective hydrogenation of acetylenes would have been motivated to modify the catalyst of Johnson by: (1) providing a catalyst wherein less than 80 weight percent of the silver is present in the skin periphery, and (2) incorporating the use of an alkali metal component, e.g. potassium in the range of about 0.01 to 10 weight % of the catalyst and fluoride in an equimolar concentration with that of potassium (as taught by Cheung) in order to achieve improvements in catalyst selectivity and increase in catalyst life.

Finally, the person having ordinary skill in the art of catalysts for the selective hydrogenation of acetylene would have had a reasonable expectation of success in modifying the catalyst of Johnson to provide for a silver content in the skin periphery of less than 80 weight percent and use of an alkali metal component, e.g. potassium in the range of about 0.01 to 10 weight % of the catalyst and fluoride in an equimolar concentration with that of potassium (as taught by Cheung) because (1) Johnson discloses wherein the silver may be "distributed *throughout* the catalyst in any suitable manner," (2) both Johnson and Cheung are concerned with catalysts for the selective hydrogenation of unsaturated hydrocarbons, (3) both Johnson and Cheung propose use of a silver/palladium hydrogenation catalyst, and (4) it is known in the art that silver/palladium/alkali metal catalysts are highly effective for the hydrogenation of highly unsaturated hydrocarbons such as acetylene (e.g. as evidenced by Frenzel).

70. With respect to claim 42, Johnson discloses wherein the selectivity of the catalyst for the conversion of acetylene to ethylene is greater than 50 % (see Johnson, Fig. 1 and accompanying text) (see also Frenzel, Table 2 (catalyst E)).

71. With respect to claim 43, Johnson discloses wherein the palladium is less than 0.05 weight % of the catalyst (see Johnson, column 2, lines 21-31).

72. With respect to claim 49, Johnson discloses wherein the pore volume is in a range of from about 0.24 to about 0.29 cubic centimeters per gram (see Johnson, column 2, lines 35-42).

Response to Arguments

73. Applicant's arguments with respect to all claims have been considered but are moot in view of the new ground(s) of rejection.

Conclusion

74. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Randy Boyer whose telephone number is (571) 272-7113. The examiner can normally be reached Monday through Friday from 8:00 A.M. to 5:00 P.M.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Glenn A. Caldarola, can be reached at (571) 272-1444. The fax number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for

Art Unit: 1764

published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

RPB



Glenn Calderola
Supervisory Patent Examiner
Technology Center 1700